

- (2) Any staging event, or
- (3) Any envelope expansion.

(b) A permittee must conduct each reusable suborbital rocket flight so that the reentry impact point does not loiter over a populated area.

#### § 437.61 Landing and impact locations.

For a nominal or any contingency abort landing of a reusable suborbital rocket, or for any nominal or contingency impact or landing of a component of that rocket, a permittee must use a location that—

- (a) Is big enough to contain an impact, including debris dispersion upon impact; and
- (b) At the time of landing or impact, does not contain any members of the public.

#### § 437.63 Agreements with other entities involved in a launch or reentry.

A permittee must comply with the agreements required by this section.

(a) A permittee must have an agreement in writing with a Federal launch range operator, a licensed launch site operator, or any other party that provides access to or use of property and services required to support the safe launch or reentry under a permit.

(b) Unless otherwise addressed in agreements with a licensed launch site operator or a Federal launch range, a permittee must have an agreement in writing with the following:

(1) For overflight of navigable water, a written agreement between the applicant and the local United States Coast Guard district to establish procedures for issuing a Notice to Mariners before a permitted flight, and

(2) A written agreement between the applicant and responsible Air Traffic Control authority having jurisdiction over the airspace through which a permitted launch or reentry is to take place, for measures necessary to ensure the safety of aircraft. The agreement must, at a minimum, demonstrate satisfaction of §§ 437.69(a) and 437.71(d).

#### § 437.65 Collision avoidance analysis.

(a) For a permitted flight with a planned maximum altitude greater than 150 kilometers, a permittee must obtain a collision avoidance analysis

from United States Strategic Command.

(b) The collision avoidance analysis must establish each period during which a permittee may not initiate flight to ensure that a permitted vehicle and any jettisoned components do not pass closer than 200 kilometers to a manned or mannable orbital object. A distance of less than 200 kilometers may be used if the distance provides an equivalent level of safety, and if the distance accounts for all uncertainties in the analysis.

#### § 437.67 Tracking a reusable suborbital rocket.

A permittee must—

- (a) During permitted flight, measure in real time the position and velocity of its reusable suborbital rocket; and
- (b) Provide position and velocity data to the FAA for post-flight use.

#### § 437.69 Communications.

(a) A permittee must be in communication with Air Traffic Control during all phases of flight.

(b) A permittee must record communications affecting the safety of the flight.

#### § 437.71 Flight rules.

(a) Before initiating rocket-powered flight, a permittee must confirm that all systems and operations necessary to ensure that safety measures derived from §§ 437.55, 437.57, 437.59, 437.61, 437.63, 437.65, 437.67, and 437.69 are within acceptable limits.

(b) During all phases of flight, a permittee must—

(1) Follow flight rules that ensure compliance with §§ 437.55, 437.57, 437.59, and 437.61; and

(2) Abort the flight if it would endanger the public.

(c) A permittee may not operate a reusable suborbital rocket in a careless or reckless manner that would endanger any member of the public during any phase of flight.

(d) A permittee may not operate a reusable suborbital rocket in areas designated in a Notice to Airmen under § 91.137, § 91.138, § 91.141, or § 91.145 of this title, unless authorized by:

- (1) Air Traffic Control; or